

RUCO®

The Choice of Professionals

RucoCoat Acrylic Texture is a non-asbestos, 100% acrylic texture that can serve as a base coat and texture coat to achieve a decorative finished surface over a variety of interior substrates. RucoCoat Acrylic Texture does not require a top coat. It provides a durable decorative coating that is ideal for high abuse and high traffic areas. It is mildew and flame resistant. RucoCoat Acrylic Texture is formulated to create many different texture patterns and to hide minor defects in concrete and gypsum surfaces. RucoCoat Acrylic Texture is produced as a flat coating that can be tinted to a variety of colors.



RucoCoat® Acrylic Texture

ADVANTAGES

Ultra-Low VOCs: VOC content of less than 5 g/L.
Economical: Can be used as base coat and texture coat that can be left unpainted.
Flame Resistant: Conforms to ASTM D84.
Mildew Resistant: Conforms to ASTM D3273.
Efficient: May be applied with or without tint, then left unpainted, giving you a highly durable finished surface.
Reliable: Consistent time after time.

LIMITATIONS

Allow RucoCoat Acrylic Texture base coat to dry before applying texture coat.
During storage, protect material from temperature extremes and moisture. Protect from freezing.
RucoCoat Acrylic Texture ages naturally during storage, so failure to rotate stock may produce performance problems.
Not recommended over new plaster finishes.

RECOMMENDATIONS FOR USE

SURFACES: All surfaces must be clean, dry and free from any dirt, grease or water-soluble materials.

Prime all exposed metal surfaces with a rust-inhibitive primer.

GYPNUM WALLBOARD: Maintain minimum air, product, and surface temperature of 50°F - 100°F at all times. Treat drywall joints and fastener heads with any of the Ruco Joint Compounds to a minimum Level 3 finish as specified in GA-214.

CONCRETE: Allow new concrete to cure for a minimum of 60 days. Remove oils, grease, efflorescence or other deposits. Grind unlevelled surfaces and remove dust. Treat irregularities with Ruco Sure Sand Set Type compounds.

MIXING: Stir thoroughly prior to applying. For base coat do not thin. Thin as necessary to achieve desired texture coat.

APPLICATION: RucoCoat Acrylic Texture base coat may be brushed, rolled, or applied with an airless or conventional sprayer. For best results, spray apply at 8 mils. Allow the base coat to dry for a minimum of 6 hours before applying the texture coating. Use an airless paint sprayer capable of a minimum of 1.1 gallons per minute for the base coat. Apply with a sprayer equipped with a 1/4" hose (1/8" whip optional), and a .523 tip. Spray the base coat at a minimum of 3000 psi. A hopper or other texture equipment may be used for texturing. Variation in equipment and/or technique will cause a difference in results.

continued →

Customer Service
1-800-554-9255

RUCO®

Southern Wall Products Incorporated
P.O. Box 1109
Tucker, Georgia 30085-1109
770-621-3065
www.ruco.com

RuCoat® Acrylic Texture

PRODUCT DATA

MATERIAL: Non-asbestos, acrylic formulation

TYPE: Spray machine application or hand application

PRODUCT SENSITIVITY: Do not apply in temperature below 50°F or above 100°F. Substrate must be thoroughly dry.

COVERAGE: Approximately 200 ft² / gallon for the base coat at 8 mils. The texture coat coverage will vary according to the desired texture type.

STORAGE: Store in enclosed dry storage area, both in the supplier's warehouse and on the job site.

PACKAGING

5 gallon pail

ARCHITECTURAL SPECIFICATIONS

PART 1: GENERAL

1.01 Scope -

Specify to meet project requirements.

1.02 Qualifications -

Southern Wall Products, Inc. and approved manufacturers shall manufacture all Gypsum Wallboard finishing materials. The materials shall be installed in accordance with the Association of Wall and Ceiling Industries, "Recommended Levels of Gypsum Board Finish."

1.03 Delivery and Storage -

Store in an enclosed shelter in the original unopened packages. Protect from temperatures below freezing and over 120°F.

1.04 Project Conditions -

A. Install interior gypsum wallboard finishing materials only after building is enclosed.

B. Ventilation:

1. Provide ventilation during and following joint treatment application.
2. Use temporary air circulators in enclosed areas lacking natural ventilation.
3. Allow additional drying time between coats of joint treatment, under slow drying conditions.
4. Protect installed materials from drafts during hot, dry weather.

C. Temperature:

Maintain a minimum surface, mix, and air temperature of 50°F - 100°F until all joints have dried completely.

PART II: PRODUCTS

2.01 Materials -

A. Joint Reinforcement - Ruco® Reinforcing Tapes

B. Joint Treatment

1. Ruco® Ready Mixed Joint Compounds
2. Ruco® Set Type Joint Compounds

C. Ceiling and Wall Textures

1. Ruco® Styrene Spray Textures
2. Ruco® Design Texture

D. Surface Equalizers

1. RuCoat® Equalizer
2. RuCoat® Equalizer Plus

E. Acrylic Textures

1. RuCoat® Acrylic Texture

PART III: EXECUTION

3.01 Installation -

Use all products in accordance with Southern Wall Products' printed package instructions.

3.02 Application - Joint Compound

Levels of finish are to be determined in accordance with "Recommended Levels of Gypsum Board Finish" as developed by AWCI, CISCA, GA, and PDCA. ASTM recognizes the "Recommended Levels of Gypsum Board Finish" in ASTM C840.

A. Level 1

Intended for plenum areas above ceilings, areas where assembly is concealed by final construction, smoke barriers, and separation walls in attic.

B. Level 2

Intended for water resistant gypsum board for tile substrate, garages, warehouses, and other areas where appearance is not of primary concern.

C. Level 3

Intended for appearance areas receiving heavy or medium texture finishes or where heavy grade wallcoverings are to be applied as final finish.

D. Level 4

Intended for appearance areas receiving flat paints, light texture finishes, or light or medium weight wallcovering.

E. Level 5

Intended for appearance areas receiving flat, low-luster, semi-gloss, gloss, or enamel finish paints or coatings, light texture finishes, light or medium weight wallcovering, un-backed vinyl wallcoverings, or severe light conditions.

CLEANUP: Wipe up drips and spills immediately with a wet cloth. Clean tools with soap and water. Close container after each use.

PRECAUTIONS: If dry-sanding or otherwise working in a dusty environment containing this material, ventilate or use a dust collector. It is also recommended that eye protection and a respirator, which is NIOSH approved, be worn when spraying. Wet sanding or sponging finished joints is recommended to avoid creating dust.

WARRANTY: Job conditions and methods of application such as: temperature, humidity, and over-thinning are beyond the control of SWP Inc. Its warranties of fitness and merchantability as well as any other warranties expressed or implied shall be effective if this product is applied according to SWP Inc. directions and specifications. Maximum liability shall be limited to replacement of material only.

TINTING: Acrylic Texture is a flat coating available in a variety of tint colors.

ACRYLIC TEXTURE



KNOCKDOWN TEXTURE WITH KHAKI TINT

SUBMITTAL APPROVAL

Job Name: _____

Job Location: _____

Contractor: _____

Approved By: _____

Title: _____

Date: _____

Stamps and Signatures:

| |
|--|
| |
|--|